

FGA4000XDS Gas Analyzer

Accurate · Portable · Fast · Dynamic

FGA4000XDS Features:

- Quick 2 second response time
- Six large LED displays
- Measures 5 gases: HC, CO, CO₂, O₂, and NOx*
- Measures RPM* for 2 or 4 stroke engines
- Calculates AFR and Lambda
- Built-in real-time clock and data recorder
- Internal/External printer

*Optional Equipment



ALL-IN-ONE FAST PERFORMING DIAGNOSTIC TOOL

When you need a reliable gas analyzer that can accurately speed up your emissions, tune-ups, and diagnostics testing, the FGA4000XDS is the perfect answer. By offering immediate results in seconds, the FGA4000XDS Gas Analyzer is the **fastest machine** on the market. Certified to BAR and OIML standards, this gas analyzer provides a portable, accurate, and quick solution for every tune-up and automotive mechanic shop.

The FGA4000XDS measures up to five gases, including Hydrocarbons (HC), Carbon Monoxide (CO), Carbon Dioxide (CO₂), Oxygen (O₂), and optionally Oxides of Nitrogen (NOx). The analyzer's six super-bright, oversized LED displays make it easy to see and read. The FGA4000XDS can be read from 25 feet away in both dark and sunlit environments. The features in the FGA4000XDS allow you to diagnose or tune virtually any fuel-related issue quickly and accurately, maximizing the efficiency of your technician and minimizing your customer's down-time.

The FGA4000XDS instantaneously displays gas readings and calculates Air to Fuel Ratio (AFR), Lambda (λ), and Grams per Mile (GPM) or Grams per Kilometer (GPK) in real time. With the optional tachometer attached, engine speeds of up to 30,000 RPM can be read and recorded. The optional printer allows shop owners to print their customer's test results or diagnostic findings onto a customizable print-out. The print-out displays your company's name, information, date, time, and all of the gas readings, providing a permanent record for both you and your customer.

For those shops providing performance tuning, an optional analog output allows the connection of a dynamometer, chart recorder, or data acquisition console to conveniently display all essential information on to a single monitor.

The FGA4000XDS can measure exhaust gases from two tail pipes and gives you the average reading, or can set up an exhaust dilution. This feature will not only warn you when there is a leak in your exhaust system, it will also alert you when the exhaust probe is not fully inserted in the tailpipe.

The FGA4000XDS is portable. Plug it into a cigarette lighter or accessory jack and view real-world engine performance and driving conditions on a road test. For extended in-shop use, the analyzer can be plugged into a standard 110 or 230 VAC. You can use the internal record feature to store all eight values and download the information to a PC when you return or replay the information directly to the analyzer display. Instead of spending hundreds or thousands of dollars for a dynamometer or test cell, you can now achieve real-world results right from the driver's seat of the car.

The FGA4000XDS is a cost-effective, all-in-one performer, which makes it the perfect trouble-shooting tool for your diagnostic needs. Automotive, motorcycle, or any exhaust emissions are ideal applications where detection of up to 5 gases is required.

Infrared Industries was the first company to develop a gas analyzer for automotive use. This patented revolutionary analyzer was used exclusively by Sun, Bear, Allen Test, and other companies throughout the 1970s and 1980s. With over 40 years experience in developing and manufacturing gas analyzers for the industrial, automotive, petroleum, utilities, analytic, and environmental industries, you can be assured that Infrared Industries has the knowledge and know-how to produce the finest automotive analyzer available today.

FGA4000XDS Gas Analyzer



The FGA4000XDS Gas Analyzer features a dual-filtering system that filters both heavy and light contaminants and water, allowing the analyzer to perform well in the harshest environments.

FGA4000XDS Highlights:

- Dual exhaust measurement
- Exhaust dilution warning
- Auto-zero for maintaining high accuracy
- Flow indicator
- Pump switch for gas purging
- Custom print-outs with user-selectable header text (*optional*)

SPECIFICATIONS

Gases and Ranges (within 1% full-scale accuracy)

HC	Hydrocarbons (n-Hexane)	0-10,000 PPM
CO	Carbon Monoxide	0-10%
CO ₂	Carbon Dioxide	0-20%
O ₂	Oxygen	0-25%
NO _x	Oxides of Nitrogen	1-5,000 PPM
TACH	Tachometer (Displayed as kRPM = 1,000 RPM)	0-30,000 RPM
AFR	Air to Fuel Ratio	0-50%
λ	Lambda	0-5
GPM	Grams per Mile	
GPK	Grams per Kilometer	

Display

Six windows with 0.8" super-bright 4-digit LEDs
Displays HC, CO, CO₂, O₂, NO_x, AFR, λ, kRPM, and GPM user-selectable

Principle

HC, CO, CO₂ – Non-dispersive Infrared (NDIR)
O₂, NO_x – Electrochemical Cell

Accuracy

BAR-90 certified
Meets BAR-97 performance specifications
Canada's AirCare Certified
Meets or exceeds OIML Class I Gas standards

Warm-Up Time

Five minutes or less

AC Power

110 VAC / 220 VAC +/- 10%, 50/60 Hz
0.5A / 0.3A max
AC voltage range 90V - 240V

DC Power

10 VDC - 16 VDC
1.5A nominal, 3.5A max

Weight

9 Lbs. (4.1 kg)

Size (W x L x D)

13.2" x 10.8" x 6.5"
33.5 cm x 27.4 cm x 16.5 cm

Temperature

2°C to 45°C (35.6°F to 113°F) Operating
-40°C to 75°C (-40°F to 167°F) Storage

Interface

Eight analog outputs 0-1 VDC, 0-5 VDC, or 0-10 VDC – Specify when ordering
RS232 with custom protocol
DLL provided upon request

Warranty

One year standard
Extended warranty available

Accessories

Included

Oxygen sensor
Flexible probe
25' Sampling hose
AC/DC power cable plus fuse
Owner's Manual
Quick Reference Guide

Optional

Internal/External printer
NO_x sensor
Inductive tachometer pick-up
2-shelf or 3-shelf rolling cart

Motorcycle Fittings

2, 4, and 6 cylinder manifolds
6mm fitting for Honda, Yamaha, or Kawasaki
10mm fitting for Ducati

Optional Software

Dynamic Link Library (DLL) for custom software development
Menus in plain English
Easy-to-use, menu-driven, Windows-based software